




SURFACE MOUNTED PANIC BOLT WITH PUSH PAD



OPERATION

Pressing the push pad, which has the instruction PUSH on the point of use, immediately retracts the locking shoots at the top and bottom on the leading edge of the door. This emergency panic exit device allows for fast, single action operation to open the door. The unique light action automatic bolting upon door closure is fitted as standard. The independently sprung bolts are steel, non-tapered with a 23mm throw, offering a high level of safety without compromising on security.



APPLICATIONS

Suitable for use in areas where occupants are likely to be familiar with the operation of the emergency exit device. The light action for ease of escape makes the MICO two point locking with push pad actuator ideal for many applications. Examples include, use by the elderly, disabled, private offices, and small workshops.

For use on single doors, and double doors with plain meeting stiles.

Conforms to all the requirements of BS EN 179 Certified to CE No. 37601341B

DIMENSIONS

Standard height of 2150mm (can be reduced on site to suit)
 Extension kits also available, increasing the height to 3000mm
 Push plate width = 800mm (suitable for door widths 925mm - 1300mm)
 Other widths readily available to order (push plate can be cut to size on site or in a workshop)
 Mechanism zinc plated steel. External housings are aluminium.

HANDING

This unit is handed (LH and RH)

OPTIONS

- Microswitching**
- Key Dogging**
- External Access**
- Double Doors**

Finishes

To order specify: 942P MS (self handing)
 To order specify: 942P DC
 See optional accessories.
 Order 2 x MICO 942P on double doors with plain meeting stiles.
 SAA finish supplied as standard. Wide range of other metallic and coloured (RAL) finishes available. Please ask for details.

Drawing Not to Scale.

